Barcode Scanner

User Manual

11D,12D,82D-V2.1

Table of contents

End Mark	1
Buzzer Setup	2
Reverse Code Reading	3
Duplicate Barcode Upload Setup	3
Invoice Function	4
Interface setup	4
Language Setup	4
CODE128	7
EAN 8	7
EAN 13	8
UPC-E0	8
UPC-A	9
Interleaved 2 of 5	11
MATRIX 25	11
CODE 39	11
CODE 32	12
CODABAR	13
CODE 93	14
CODE 11	14
ISBN	14
ISSN	14
INDUSTRIAL25	15
STANDARD25	15
MSI_Plessey	15
QR	15
PDF417	16
Aztec	16
DataMatrix	16
MicroPDF417	16
MicroQR	16
Add Prefix	17
Add Suffix	17
Delete Characters	18
Appendix 1: Parameter Code	19
Appendix 2:ASCII	21



Buzzer Setup				
Volume-ON*	USA Volume-OFF			
日常語	Low Volume			
Trigge	r Mode			
Continuous Mode	Auto-Sensing Mode			
Capital & Low	vercase Setup			
No Swap*	EXACULAR EXACULAR Swap			
All Lowercase	All Capital			

Reverse Code Reading Turning on this setting will affect the scanning speed, please turn it on while you need to use				
Duplicate Barco	de Upload Setup			
Duplicate Detection-ON	Duplicate Detection-OFF*			
(Auto-Sensing Mode)	(Auto-Sensing Mode)			
Delay forever	Delay 3s			
(Auto-Sensing Mode)	(Auto-Sensing Mode)			
Duplicate Detection-ON	Duplicate Detection-OFF*			
(Continue Scan Mode)	(Continue Scan Mode)			
Delay forever	Delay 3s			
(Continue Scan Mode)	(Continue Scan Mode)			













Check Digit-OFF	Check Digit-ON
2 Extra Code-OFF	2 Extra Code-ON
5 Extra Code-OFF	5 Extra Code-ON
System Digit-OFF	System Digit-ON
UPCA to EAN13-OFF	UPCA to EAN13-ON

















Delete Characters				
Delete Characters-OFF	Delete Characters-ON			
Before Barcode	After Barcode			
E.g. The bar code content is "123456789", if you want to set the scanner to delete the number 1, "23456789" will be shown. Please scan the following code in order: "Delete Characters-ON">"Before Barcode">"Parameter Code "0">"Parameter Code "0"<"Parameter Code "1">"Parameter Code "0"<"Parameter Code "1">"Parameter Code "1"				





Appendix 2:ASCII

He	De	Description	He	De	Descriptio	He	De	Descript
00	0	NUL	2B	43	+	56	86	V
01	1	SOH	2C	44	,	57	87	W
02	2	STX	2D	45	—	58	88	Х
03	3	ETX	2E	46	0	59	89	Y
04	4	EOT	2F	47	/	5A	90	Z
05	5	ENQ	30	48	0	5B	91	[
06	6	ACK	31	49	1	5C	92	/
07	7	BEL	32	50	2	5D	93]
08	8	BS(Backspac	33	51	3	5E	94	^
09	9	HT(Tab)	34	52	4	5F	95	_
0A	10	LF(CTRL J)	35	53	5	60	96	
0B	11	VT(CTRLK)	36	54	6	61	97	а
0C	12	FF(CTRLL)	37	55	7	62	98	b
0D	13	CR(Enter)	38	56	8	63	99	с
0E	14	SO(CTRL N)	39	57	9	64	10	d
0F	15	SI(CTRLO)	3A	58	:	65	10	е
10	16	DLE(CTRLP)	3B	59	-	66	10	f
11	17	DC1(CTRL Q)	3C	60	<	67	10	g
12	18	DC2(CTRL R)	3D	61	=	68	10	h
13	19	DC3(CTRL S)	3E	62	>	69	10	i
14	20	DC4(CTRLT)	3F	63	?	6A	10	j
15	21	NAK(CTRL U)	40	64	@	6B	10	k
16	22	SYN(CTRL V)	41	65	A	6C	10	I
17	23	ETB(CTRL W)	42	66	В	6D	10	m
18	24	CAN(CTRL X)	43	67	С	6E	11	n
19	25	EM(CTRL Y)	44	68	D	6F	11	0
1A	26	SUB(CTRL Z)	45	69	E	70	11	р
1B	27	ESC(ESC)	46	70	F	71	11	q
1C	28	FS(CTRL \)	47	71	G	72	11	r
1D	29	GS(CTRL])	48	72	Н	73	11	s
1E	30	RS(CTRL ^)	49	73	I	74	11	t
1F	31	US(CTRL_)	4A	74	J	75	11	u
20	32	(space)	4B	75	K	76	11	v
21	33	!	4C	76	L	77	11	w
22	34		4D	77	M	78	12	x
23	35	#	4E	78	N	79	12	У
24	36	\$	4F	79	0	7A	12	z
25	37	%	50	80	Р	7B	12	{
26	38	&	51	81	Q	7C	12	ì
27	39	'	52	82	R	7D	12	}
28	40	(53	83	S	7E	12	~
29	41)	54	84	Т	7F	12	DEL
2A	42	*	55	85	U			